

Study on Characteristics of Ricinoleic as a Phase Change Material

by Firman Firman

Submission date: 14-Feb-2022 07:35AM (UTC+0000)

Submission ID: 1761992767

File name: on_Characteristics_of_Ricinoleic_as_a_Phase_Change_Material.pdf (1.86M)

Word count: 4133

Character count: 22703

Log In (</Account/LogOn?ReturnUrl=%2FAMM.818%2Fbook>)

中文 (<http://zh.scientific.net/AMM.818/book>)



[Subscriptions](#) [For Editors](#) [Distributors](#) [Downloads](#) [My Cart](#)
[\(/Account/Sut\)](/Account/Sut) [\(/Info\)](/Info) [\(/Distributor\)](/Distributor) [\(/Downloads\)](/Downloads) [\(/Payment/Ca\)](/Payment/Ca)

MAIN THEMES

Energy Saving and Environmentally Friendly Technologies - Concepts of Sustainable Building Vol. 824
[\(/AMM.824/book\)](/AMM.824/book)

Current Solutions in Mechanical Engineering Vol. 823
[\(/AMM.823/book\)](/AMM.823/book)

Automotive and Transportation Engineering Vol. 822
[\(/AMM.822/book\)](/AMM.822/book)

Engineering Mechanics 2015 Vol. 821
[\(/AMM.821/book\)](/AMM.821/book)

Advanced Architectural Design and Construction Vol. 820
[\(/AMM.820/book\)](/AMM.820/book)

Advances in Heat Transfer, Flow Engineering and Energy Installations Vol. 819
[\(/AMM.819/book\)](/AMM.819/book)

Progress in Energy and Thermal Sciences Vol. 818
[\(/AMM.818/book\)](/AMM.818/book)

Propulsion Systems, Mechatronics and Communication Vol. 817
[\(/AMM.817/book\)](/AMM.817/book)

Applied Mechanics and

Home ([/](#)) > Applied Mechanics and Materials (</AMM>) > Progress in Energy and Thermal Sciences

Progress in Energy and Thermal Sciences

Volume 818

doi: [10.4028/www.scientific.net/AMM.818](https://doi.org/10.4028/www.scientific.net/AMM.818)

Papers (</AMM.818>)

Book
(</AMM.818/book>)

Info

ISBN-13: 978-3-03835-669-1

Authors / Mazlan Abdul Wahid and Mohd Fairus

Editors: Mohd Yasin

Category: Selected, peer reviewed papers from the International Conference on Energy and Thermal Sciences (ICETS 2014), October 1, 2014, Skudai, Malaysia

Pages: 322

Year: 2016

Edition: softcover

TOC: [Table of contents \(/AMM.818.toc.pdf\)](/AMM.818.toc.pdf)



Description

Collection of selected, peer reviewed papers from the International Conference on Energy and Thermal Sciences (ICETS 2014), October 1, 2014, Skudai, Malaysia.

Mechatronics II Vol. 816
(/AMM.816/book)

**Design and Development
of Sustainable
Manufacturing Systems
Vol. 815**
(/AMM.815/book)

**Advances in Mechanical
Engineering Vols. 813-814**
(/AMM.813-814/book)

**Evolution of Green Energy
and Vehicle Technology
Vol. 812**

(/AMM.812/book)

**Advanced Research in
Aerospace Engineering,
Robotics, Manufacturing
Systems, Mechanical
Engineering and
Biomedicine Vol. 811**
(/AMM.811/book)

The 45 papers are grouped as follows:

Chapter 1: Materials Engineering

Chapter 2: Technologies of Materials Processing in Manufacturing Engineering

Chapter 3: Fluids and Thermal Engineering

Chapter 4: Engines and Fuels

Chapter 5: Research and Design of Industrial Equipments and Machines

Chapter 6: Industrial Engineering

Keywords: Fluids and Thermal Engineering, Engines, Machies and industrial Equipment, Industrial Engineering

Review from Ringgold Inc., ProtoView: Editors Wahid and Yasin present readers with a collection of peer-reviewed papers selected from research presented at the International Conference on Energy and Thermal Sciences held in October of 2014 in Skudai, Malaysia. The editors have organized the selections that make up the main body of the text in six chapters devoted to applied thermodynamics and heat transfer, industrial electrical power machines and systems, power transmission lines and electrical supply, and other related subjects. Individual contributions are focused on the use of energy in lighting and other power systems in buildings, biotechnologies at use in other building systems, and a wide variety of topics

Ringgold Subjects:

- Electrical
- Engineering
- Physics
- Thermodynamics

Buy this volume

Version	ISBN	Quantity	Price
Print	978-3-03835-	1	€
	669-1		130,00
CD	978-3-03859-	1	€
	465-9		130,00
CD+Print*	978-3-03835-	1	€
	669-1		182,00
eBook**	978-3-0357-	1	€
	0150-0		130,00

ADD TO CART

Progress in Energy and Thermal Sciences

Volume 818

doi: 10.4028/www.scientific.net/AMM.818

Papers

Book

1 2 3 4 5 >

Paper Title

Page

Preface and Committee

1 Laminar and Turbulent Natural Convection Simulation with Radiation in Enclosure

Authors: M. Hussen Hasanen, Hussein J. Akeiber

Chapter 1: Applied Thermodynamics and Heat Transfer

1
Abstract: Several features of heat transfer on enclosing surfaces are discussed including temperature distributions in a room heated by a floor heater.... 3

8 The Effect of Base Fluid Type in Nanofluids for Heat Transfer Enhancement in Microtubes

Authors: Bassam H. Salman, Hussein A. Mohammed, Akeel S. Kherbeet

Chapter 1: Applied Thermodynamics and Heat Transfer

Abstract: In this paper, single phase model was used to investigate the effect of base fluid in enhancing the heat transfer for forced convection flow... 12

Pressure Drop of Two-Phase Flow Boiling with R-22 and R-290 in 7.6 mm Diameter Tube

Authors: Agus Sunjarianto Pamitran, Nasruddin, Helmi Dadang Ardiansyah, Muhammad Idrus Alhamid

Chapter 1: Applied Thermodynamics and Heat Transfer

Abstract: The characteristics of two-phase flow boiling of R-290 are required for replacing R-22 that has been phased-out. The present study focuses on... 23

Design and Thermodynamic Study of a Novel Two- Sleeve Rotary Compressor

Authors: Y.A. Alduqri, Md Nor Musa, Z.A.B. Ahmad

Chapter 1: Applied Thermodynamics and Heat Transfer

Abstract: This paper introduces a novel two-sleeve rotary compressor (TSRC) concept. The compressor mechanism is 28

basically that of a rotary motion...

Study on Characteristics of Ricinoleic Acid as a Phase Change Material

Authors: Firman, I.N.G. Wardana, Sudjito Soeparman, Nurkholis Hamidi

Chapter 1: Applied Thermodynamics and Heat Transfer

Abstract: Today the use of fatty acids as heat storage substance is growing. The use of several types of fatty acids such as oleic acid, palmitic acid,...

39

9 Single-Line to Ground-Fault Detection for Unit Generator-Transformer Based on Wavelet Transform and Neural Networks

Authors: Ahmad Rizal Sultan, Mohd Wazir Mustafa, Makmur Saini

Chapter 2: Industrial Electrical Power Machines and Systems

Abstract: This paper proposes an approach for the detection of the single line to ground fault on a unit generator-transformer, based on the extraction...

47

Performance of PI Controller Based Dynamic Voltage Restorer for Power Quality Improvement

Authors: Faridullah Kakar, Abdullah Asuhaimi bin Mohd Zin, Mohd Hafiz bin Habibuddin

Chapter 2: Industrial Electrical Power Machines and Systems

Abstract: Voltage sag and harmonics are the most frequent power quality problems faced by industrial and commercial customers today. Situation has been...

52

Statistical Analysis of Breakdown Voltages in Virgin and Aged LDPE Using Johnson S_B and Weibull Distribution

Authors: Nurul A. Bani, Zulkumain Abdul-Malek, Hussein Ahmad

Chapter 2: Industrial Electrical Power Machines and Systems

Abstract: Polymeric material such as low density polyethylene (LDPE) has been used for decades as insulating material. Any polymeric material will...

58

Review of Oil-Filled Transformer Monitoring Technology for New User

Authors: Nor Asiah Muhamad, Hanafiah Kamarden

Chapter 2: Industrial Electrical Power Machines and Systems

Abstract: Distribution and power transformer is the essential part of electrical power transmission system. Abnormalities occur at the transformer can

PAPER TITLES

Search

Laminar and Turbulent Natural Convection Simulation with Radiation in Enclosure p.3
(/AMM.818.3)

The Effect of Base Fluid Type in Nanofluids for Heat Transfer Enhancement in Microtubes p.12
(/AMM.818.12)

Pressure Drop of Two-Phase Flow Boiling with R-22 and R-290 in 7.6 mm Diameter Tube p.23
(/AMM.818.23)

Design and Thermodynamic Study of a Novel Two-Sleeve Rotary Compressor p.28
(/AMM.818.28)

Study on Characteristics of Ricinoleic Acid as a Phase Change Material p.39
(/AMM.818.39)

Single-Line to Ground-Fault Detection for Unit Generator-Transformer Based on Wavelet Transform and Neural Networks p.47
(/AMM.818.47)

Performance of PI Controller Based Dynamic Voltage Restorer for

Home (/) > Applied Mechanics and Materials (/AMM) > Progress in Energy and Thermal Sciences (/AMM.818) > Study on Characteristics of Ricinoleic Acid as a...

Paper Title: Study on Characteristics of Ricinoleic Acid as a Phase Change Material

Abstract

Today the use of fatty acids as heat storage substance is growing. The use of several types of fatty acids such as oleic acid, palmitic acid, and stearic acid as heat storage materials has been studied. But, ricinoleic acid from castor oil has not been studied yet. This study was conducted to ascertain the characteristics of ricinoleic acid as a heat storage material. Methyl ricinoleic was obtained through transesterification of castor oil by methanol with sodium methoxide catalyst. Methyl ricinoleic was then hydrolyzed using sodium hydroxide in ethanol to produce ricinoleic acid. Ricinoleic acid was identified by FTIR (Fourier Transform Infrared Spectrophotometer) test standard ASTM E 1252-07 and chemical composition was determined by Gas Chromatography-Mass Spectrometry (GC-MS). The identification of the type, amount, and environment of hydrogen in the compound was determined by Nuclear Magnetic Resonance (NMR). The analysis on characteristics, that is, transition and melting temperatures of material was performed by DSC (Differential Scanning Calorimetry) test standard ASTM D 3419-08. Based on the results of FTIR, GC-MS, ¹H-NMR, and ¹³C-NMR tests, the spectra that were obtained indicated that the test substances were methyl and ricinoleic acid 70.349%. And, the results of DSC tests indicated that the characteristics of ricinoleic acid absorbed and released latent heat at the temperature from 8.58°C and absorbed sensible heat at the temperature from -7.17°C to 8.58°C.

Info

Power Quality Improvement p.52 (/AMM.818.52)

Statistical Analysis of Breakdown Voltages in Virgin and Aged LDPE Using Johnson S_B and Weibull Distribution p.58 (/AMM.818.58)

Review of Oil-Filled Transformer Monitoring Technology for New User p.63 (/AMM.818.63)

Periodical	Applied Mechanics and Materials (/AMM) (Volume 818)
Main Theme	Progress in Energy and Thermal Sciences (/AMM.818)
Chapter	Chapter 1: Applied Thermodynamics and Heat Transfer
Edited by	Mazlan Abdul Wahid and Mohd Fairus Mohd Yasin
Pages	39-43
DOI	10.4028/www.scientific.net/AMM.818.39
Citation	Firman, I.N.G. Wardana, S. Soeparman, N. Hamidi, "Study on Characteristics of Ricinoleic Acid as a Phase Change Material", <i>Applied Mechanics and Materials</i> , Vol. 818, pp. 39-43, 2016
Online since	January 2016
Authors	Firman (/author) *, I.N.G. Wardana (/author/I_N_G_Wardana_1), Sudjito Soeparman (/author/Sudjito_Soeparman), Nurkholis Hamidi (/author/Nurkholis_Hamidi)
Keywords	Castor Oil (/keyword/Castor_Oil), Phase Change Materials (PCM) (/keyword/Phase_Change_Materials_PCM), Ricinoleic Acid (/keyword/Ricinoleic_Acid), Thermal Storage (/keyword/Thermal_Storage)
Export	RIS (/AMM.818.39.ris), BibTeX (/AMM.818.39.bib)
Price	€ 30,00



ADD TO CA

Share

* Corresponding Author

Related Articles**Useful Links**

SUBSCRIPTIONS

[\(/ACCOUNT/SUBSCRIPTIONS\)](#) [\(/SSP.250\)](#)FOR EDITORS [\(/INFO\)](#)

LOG IN

[\(/ACCOUNT/LOGON?](#)RETURNURL=%2FAMM.818.39) [and Experiments \(/DDF.367\)](#)[MY CART](#)[\(/PAYMENT/CART\)](#)[SEARCH](#)[\(/PAPERSEARCH.ASPX\)](#)[CONTACT US](#)[\(/HOME/CONTACTS\)](#)[TERMS AND CONDITIONS](#)[\(/HOME/TERMSANDCONDITIONS\)](#)[POLICY AND ETHICS](#)[\(/HOME/POLICYANDETHICS\)](#)[CONFERENCE ETHICS](#)[AND QUALITY CONTROL](#)[\(/HOME/CONFERENCEETHICSANDQUALITYCONTROL\)](#)

DISTRIBUTORS

[\(/DISTRIBUTOR\)](#)

DOWNLOADS

[\(/DOWNLOADS\)](#)

ABOUT US

[\(/HOME/ABOUTUS\)](#)[SITEMAP](#)[\(/HOME/SITEMAP\)](#)**Recent Themes**

- Fracture and Fatigue of Materials and Structures [\(/SSP.250\)](#)
- Flow Phenomena: Fluids, Heat and Mass [\(/DDF.366\)](#)
- Diffusion Phenomena: Aspects of Characterization and Experiments [\(/DDF.367\)](#)



Scientific.Net
By Trans Tech Publications Ltd

Scientific.Net is a registered
brand of Trans Tech Publications
Inc.

2016 by Trans Tech Publications
Inc. All Rights Reserved

Study on Characteristics of Ricinoleic Acid as a Phase Change Material

Firman^{1,a}, ING Wardana^{2,b}, Sudjito Soeparman^{2,c}, Nurkholis Hamidi^{2,d}

¹Mechanical Engineering Department, Politeknik Negeri Ujung Pandang, Makassar, Indonesia

²Mechanical Engineering Department, Engineering Faculty, Universitas Brawijaya, Malang, Indonesia

^afirmananoor@yahoo.com, ^bwardana@ub.ac.id, ^csudjitospn@yahoo.com,
^dnurkholishamidi@yahoo.com

Keywords: phase change material, thermal storage, ricinoleic acid, castor oil

Abstract Today the use of fatty acids as heat storage substance is growing. The use of several types of fatty acids such as oleic acid, palmitic acid, and stearic acid as heat storage materials has been studied. But, ricinoleic acid from castor oil has not been studied yet. This study was conducted to ascertain the characteristics of ricinoleic acid as a heat storage material. Methyl ricinoleic was obtained through transesterification of castor oil by methanol with sodium methoxide catalyst. Methyl ricinoleic was then hydrolyzed using sodium hydroxide in ethanol to produce ricinoleic acid. Ricinoleic acid was identified by FTIR (Fourier Transform Infrared Spectrophotometer) test standard ASTM E 1252-07 and its chemical composition was determined by Gas Chromatography-Mass Spectrometry (GC-MS). The identification of the type, amount, and environment of hydrogen in the compound was determined by Nuclear Magnetic Resonance (NMR). The analysis on characteristics, that is, transition and melting temperatures of material was performed by DSC (Differential Scanning Calorimetry) test standard ASTM D 3419-08. Based on the results of FTIR, GC-MS, ¹H-NMR, dan ¹³C-NMR tests, the spectra that were obtained indicated that the test substances were methyl and ricinoleic acid 70.349%. The results of DSC tests indicate that the characteristics of ricinoleic acid absorbed and released latent heat at the temperature from 8.58°C and absorbed sensible heat at the temperature from -7.17°C to 8.58°C.

Introduction

Currently the energy needs in the industrial and building sectors is getting increased. As a result, the impact on the environment is increasing as well. On the other hand, the world is running out of energy supply which will eventually run out. Therefore, an important step is required to develop more efficient technology that is environmentally friendly.

Some research in the field of energy conservation has been carried out in order to obtain such a technology. Thermal energy storage in the form of sensible heat and latent heat becomes important aspect of energy conservation [1]. One of the rapid technological developments is latent heat utilization applications. Latent heat storage is one of the most efficient ways to store thermal energy [2]. To take advantage of latent heat, heat storage materials are required. The process of heat storage takes place during phase change process. There are four kinds of phase changes; they are solid-gas, liquid-gas, solid-solid, and solid-liquid. The processes of sublimation (solid-gas) and evaporation (liquid-gas) are followed by a large volume change of materials, so that it is impractical for latent heat storage. On the other hand, solid-solid phase transformations are accompanied by small density changes, but the transformation has a low latent heat. Therefore, the heat storage process widely used is the one that takes place at solid-liquid phase change. The material used as a latent heat storage medium is known as phase change material (PCM).

In the last 20 years more than 150 kinds of PCM technologies have been made and about 45 of them with both organic and inorganic materials have already been available commercially [4]. Latent heat storage using a PCM is an effective way to store thermal energy. The advantage of this method is that it has a high energy storage density and its storage process goes through isothermal method [5,6]. PCM is also suitable for different applications such as heating and cooling rooms [7].

Some inorganic materials used as PCM, among others, are calcium chloride hexhydrate and calcium chloride tetrahydrate, while organic materials, among others, are paraffin, lauric acid, and palmitic acid. Lauric acid is produced from coconut oil fatty acids, whereas palmitic acid is from palm oil fatty acids. The use of fatty acids as PCM allows storing large thermal energy in a small density [8]. PCM and organic materials have advantages, among others, they freeze quickly, or without supercooling; their composition is unchangeable; and they are not hazardous [9]. Meanwhile, research on the characteristics of ricinoleic acid from castor oil as PCM has not been previously conducted.

Fatty acid from castor oil contains ricinoleic acid 89.5%, linoleic acid 4.2%, Oleic acid 3.0%, stearic acid 1.0%, palmitic acid 1.0%, dehydroxystearic acid 0.7%, linolenic acid 0.3%, and eicosanoic acid 0.3% [10]. The composition implies that ricinoleic acid is much more dominant than other fatty acids of castor oil. In addition, ricinoleic acid is not corrosive to container materials, is eco-friendly, and available in markets. Based on these properties, ricinoleic acid has a potential to be used as a PCM.

One of the types of natural materials in Indonesia used as a PCM, is Micro [11]. In addition to micro, a natural material that meets these criteria is ricinoleic acid produced from castor oil plant (*Ricinus communis* Linn). Ricinoleic acid has the chemical formula (12 (R)-hydroxy-9Z-octadecenoic acid) with the molecular formula $C_{18}H_{34}O_3$ [11]. However, research on its use as a PCM natural material has never been held. Therefore, it is very important to do research related to its use as a PCM. This study was conducted to determine the characteristics of ricinoleic acid as a phase change material.

Material and Method

The substances used in the study were castor oil, sodium metal, anhydrous methanol, potassium hydroxide, diethyl ether, hydrochloric acid, ethanol, sulfuric acid, sodium sulfate anhydrous, and universal indicator produced by PT Kimia Farma.

Methyl ricinoleic was obtained through a transesterification reaction of castor oil by methanol with the catalyst sodium methoxide. Methyl ricinoleic was then hydrolyzed using sodium hydroxide in ethanol to produce ricinoleic acid [13]. Ricinoleic acid was identified by using Fourier Transform Infrared Spectrophotometer (FTIR) Shimadzu FTIR Prestige-21 with the test standard ASTM E 1252-07. And the chemical composition of the substance was determined by Gas Chromatography-Mass Spectrometry (GC-MS) Agilent Type 7890 A.

Identification of hydrogen type, amount of hydrogen, and hydrogen environment in the compound was determined by Nuclear Magnetic Resonance (NMR) JEOL type JNM-ECA 500. The analysis on the characteristics of transition and melting temperatures of the materials were performed by Differential Scanning Calorimetry (DSC) with the test standard ASTM D 3419-08. The testing was carried out using 15-20 mg of ricinoleic acid with heating and cooling treatment at the temperatures of -30°C - 80°C with a heating and cooling rate $5^{\circ}\text{C}/\text{min}$.

Results and Discussion




Figure 1 Spectra of results of FTIR test on ricinoleic acid

The FTIR test on ricinoleic acid that resulted in spectra 3408 cm^{-1} indicated a functional group O-H stretch. This functional group indicates the acidic nature of substance and existed in the first carbon chain. Spectra 2926 cm^{-1} and 2854 cm^{-1} were aliphatic C-H functional groups. The C-H functional groups were located at C9 and C10 of carbon double bonds (unsaturated). The functional groups also indicated a double bond of cis like the nature of fatty acids in general [14]. Spectra 1710 cm^{-1} was the functional group C = O stretch. As the functional groups O-H, the functional groups C=O were also attached to first chain and indicated an acid nature. Spectra 1462 cm^{-1} was functional group CH₂ and CH₃. The functional group CH₂ was attached to each saturated carbon chain while CH₃ was to carbon chain C18. Spectra 1247 cm^{-1} to 1039 cm^{-1} were C-O functional groups. The first C-O functional group was strongly alleged the hydroxyl group at C12 chain. The hydroxyl group is the hallmark of ricinoleic acid [12]. The second CO functional group was alleged to derive from solvent. Spectra 941 cm^{-1} was the functional group of aliphatic NO; spectra 725 cm^{-1} was the functional group CH; and spectra 351 cm^{-1} was suspected of impurities. Ricinoleic acid samples were then tested by GC-MS and the results obtained are shown in Figure 2.




Figure 2 Spectra of results of GC-MS test (a) Structural formula of Ricinoleic acid (b)

GC-MS tests brought about methyl composition and ricinoleic acid 70.349% and the remaining was of other fatty acid and impurities. Next, ¹H-NMR dan ¹³C-NMR tests were conducted to identify the kinds, amount, and environment of hydrogen in ricinoleic acid compound. The results are shown in the following Figure 3.




Figure 3 Spectra of results of ¹H- NMR test

Data ¹H-NMR: (CDCl₃, 125 MHz), δ (ppm); 0,893191 (18-H, 3H, t); 1,2926 (CH₂, 16H, m); 1,4612 (13-H, 2H, m); 1,6026 (3-H, 2H, m); 2,0397 (8-H, 2H, m); 2,1928 (-OH, 1H, s); 2,2966 (11-OH, 2H, t); 2,7674 (2-H, 2H, t); 3,5392(12-H, 1H, m); 4,8778 (-OCH₃, 3H, s); 5,4317 (9-H, 1H, m); 5,7767 (10-H, 1H, m).




Figure 4 Spectra of results of ^{13}C -NMR test

21
 Data ^{13}C -NMR (CDCl_3 , 125 MHz), δ (ppm); 175,9563 (C=O); 140,1684 (C-10); 132,6331 (C-9); 127,0437 (C-1); 72,6179 (C-12); 30,7923 (O-CH3); 30,6588 (C-13); 30,3249 (C-2); 26,1185 (C-17); 14,5962 (C-18). The results of ^1H -NMR and ^{13}C -NMR tests indicated that the number of hydrogen and carbon atoms and their positions strongly justified the results of FTIR and GC-MS tests.




Figure 5 Temperature characteristics of ricinoleic acid

The DSC tests on ricinoleic acid resulted in heat absorbance characteristics with a melting temperature 8.58°C , onset temperature -6.01°C , crystallization temperature -7.17°C , and heat fusion 3.35°C . A crystallization taking place below a melting temperature implied that in the process of ricinoleic acid crystallization a supercooling happened despite its small size. This was in line with what Mehling [9] stated, that is, the crystallization of ricinoleic acid generally do not occur, or the supercooling is too small.

Conclusion

On the basis of the results of FTIR, GC-MS, ^1H -NMR, and ^{13}C -NMR tests, a spectra w was obtained, which indicated that the tested substances were methyl and ricinoleic acid 70.349%. The DSC test results indicated a characteristic that ricinoleic acid absorbed and released latent heat at the temperature 8.58°C and absorbed sensible heat at the temperature from -7.17°C to 8.58°C

Acknowledgements

17
 We would like to express our sincere acknowledgement to the Directorate General of Higher Education, Ministry of Education and Culture of the Republic of Indonesia for the grant though a Doctoral Dissertation Research Grant 2014.

References

- [1] Demirbas, M.F. Thermal Energy Storage and Phase Change Materials: an Overview. *Energy Sources*, part B, 1: 85-95, 2006.
- [2] Farid, M.M., A.M. Khudhair, S. A. K. Razack, S. Al-Hallaj. A Review on Phase Change Energy Storage: Materials and Applications, *Energy Conversion and Management* 45 (2004) 1597-1615.
- [3] Tyagi, V.V., D. Buddhi. PCM Thermal Storage in Buildings: A State of Art, *Renewable and Sustainable Energy Reviews* 11 (2007) 1146-1166.
- [4] Zalba, B., J.M. Marin, L.F. Cabeza, H. Mehling. Review on Thermal Energy Storage with Phase Change: Heat Transfer Analysis and Applications, *Applied Thermal Engineering*, 23 (2003) 251-283.
- [5] Sharma, S.D., K. Sagara. Latent Heat Storage Materials and Systems: A Review. *International Journal of Green Energy* 2: 1-56, 2005.
- [6] Sharma, A., V.V. Tyagi, C.R. Chen, D. Buddhi. Review on Thermal Energy Storage With Phase Change Materials and Applications, *Renewable and Sustainable Energy Review* 13 (2009) 318-345.
- [7] Medved, D., M. Kvakovsky, V. Sklenarova. Latent Heat Storage Systems. Intensive Programme "Renewable Energy Source", May 2010. Zelezna Ruda-Spicak, University of west Bohemia, Czech Republic.
- [8] Rozanna, D., A. Salmiah, I.G. Chuah, R. Medyan, T. Choong, Sa'asi, M. A Study on Thermal Characteristic of Phase Change Material (PCM) in Gypsum Board for Building Application, *Journal of Oil Palm Research* Vol. 17, June, 2005. P. 41-46.
- [9] Mehling, H., I. F. Cabeza. *Heat and cold storage with PCM: An up to date Introduction into basics and applications*, Springer-Verlag Berlin Heidelberg, 2008.
- [10] G.R.O'Shea. Company 650 East Devon Avenue, Suite 180-Itasca Illinois 60143-3142-(800) 778-7072-(630) 773-3223 Fax. (630) 773-3663 www. Groshea.com + general@groshea.com, 2011.
- [11] Hendra, R., Hamdani, T.M.I. Mahlia, H.H. Masjuki. Thermal and Melting Heat Transfer Characteristics in a Latent Heat Storage System Using Mikro, *Applied Thermal Engineering* 25 (2005) 1503- 1515.
- [12] Scrimgeour, C. Chemistry of Fatty Acids. Dalam *Bailey's International Oil and Fat Products*, Sixth Edition, Six Volume Set. Edited by Fereidoon Shahidi. Copyright@2005 John Wiley & Sons Inc.
- [13] Parlan, Isolasi Asam Risinoleat dari Minyak Jarak (*Castor Oil*) Melalui Reaksi Transesterifikasi, *Jurnal MIPA*, Tahun 26, Nomor 1, Januari 1997.
- [14] Fessenden, R.J., J.S. Fessenden. *Kimia Organik* Jilid 2 edisi ketiga, Alih bahasa: Aloysius Hadyana Pudjaatmaka, Jakarta: Erlangga, 1986.

Study on Characteristics of Ricinoleic as a Phase Change Material

ORIGINALITY REPORT

15%

SIMILARITY INDEX

9%

INTERNET SOURCES

9%

PUBLICATIONS

6%

STUDENT PAPERS

PRIMARY SOURCES

1	connection.ebscohost.com Internet Source	1%
2	repository.um.edu.my Internet Source	1%
3	Tarhan, S.. "Temperature distributions in trapezoidal built in storage solar water heaters with/without phase change materials", Energy Conversion and Management, 200609 Publication	1%
4	Submitted to Udayana University Student Paper	1%
5	(A. Shokuhfar, A. Öchsner, G. Murch and J.M.P.Q. Delgado). "Diffusion in Solids and Liquids VIII", Repositório Aberto da Universidade do Porto, 2013. Publication	1%
6	Ionela Iordan, Constantin Dogariu, Cristina Mohora. "Finite Element Analysis for Deep	1%

Drawing Process and Part Shape Optimization", Applied Mechanics and Materials, 2015

Publication

7	onlinelibrary.wiley.com Internet Source	1 %
8	Ramon Ramirez-Tijerina, Carlos Rivera-Solorio, Jogender Singh, K. Nigam. "Numerical Study of Heat Transfer Enhancement for Laminar Nanofluids Flow", Applied Sciences, 2018 Publication	1 %
9	Submitted to Universiti Teknologi Malaysia Student Paper	1 %
10	academic.oup.com Internet Source	1 %
11	mrs.org Internet Source	1 %
12	Submitted to Universitas Airlangga Student Paper	1 %
13	Submitted to Universidad de Cartagena Student Paper	<1 %
14	Submitted to CSU, San Jose State University Student Paper	<1 %
15	Submitted to Karunya University Student Paper	<1 %

- | | | |
|----|---|------|
| 16 | Raid Abid Alwan, Mazlan Abdul Wahid, Mohd Fairuse Mohd Yasin, Arkan AlTaie, Abuelnuor Abdeen Abuelnuor. "Effects of Equivalence Ratio on Asymmetric Vortex Combustion in a Low NOx Burner", International Review of Mechanical Engineering (IREME), 2015
Publication | <1 % |
| 17 | microbiologyjournal.org
Internet Source | <1 % |
| 18 | idr.mnit.ac.in
Internet Source | <1 % |
| 19 | M. Fatih Demirbas. "Thermal Energy Storage and Phase Change Materials: An Overview", Energy Sources, Part B: Economics, Planning, and Policy, 2006
Publication | <1 % |
| 20 | S.D. Sharma, Kazunobu Sagara. "Latent Heat Storage Materials and Systems: A Review", International Journal of Green Energy, 2005
Publication | <1 % |
| 21 | link.springer.com
Internet Source | <1 % |
| 22 | Jamal, , I.N.G. Wardana, Nurkholis Hamidi, and Denny Widyanuriawan. "Identification of Chemical Compound of Dammar Resin Using Various Solvents with Gas Chromatographic– | <1 % |

Mass Spectrometric Method", Applied Mechanics and Materials, 2014.

Publication

23

www.tandfonline.com

Internet Source

<1 %

24

Tay, N.H.S.. "Designing a PCM storage system using the effectiveness-number of transfer units method in low energy cooling of buildings", Energy & Buildings, 201207

Publication

<1 %

25

jonuns.com

Internet Source

<1 %

26

pubs.rsc.org

Internet Source

<1 %

27

www.ajol.info

Internet Source

<1 %

28

www.emeraldinsight.com

Internet Source

<1 %

Exclude quotes On

Exclude matches < 10 words

Exclude bibliography On

Study on Characteristics of Ricinoleic as a Phase Change Material

GRADEMARK REPORT

FINAL GRADE

/0

GENERAL COMMENTS

Instructor

PAGE 1

PAGE 2

PAGE 3

PAGE 4

PAGE 5

PAGE 6

PAGE 7

PAGE 8

PAGE 9

PAGE 10

PAGE 11

PAGE 12
